

View Online at <https://aerobasegroup.com/nsn/4730-01-540-4829>

**Thread Class:**

3a second fluid end connection

**Quick Disconnect Size:**

0.752 inches first quick disconnect end

**Maximum Operating Temp:**

275.0 degrees fahrenheit 1st response

**Connection Style:**

Push (external) first quick disconnect end

**Leg Length:**

0.657 inches

**Connection Type:**

Threaded external tube second fluid end connection

**Thready Qty Per Inch (tpi):**

16 second fluid end connection

**Maximum Operating Pressure:**

500.0 pounds per square inch 1st response

**Thread Size:**

0.750 inches second fluid end connection

**Flow Angle:**

37.0 radians

**Outside Diameter Tube Accommodated:**

0.500 inches second fluid end connection

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-225/6 federal specification single material response and qq-a-225/8 federal specification 1st material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 1 or 2 military specification single treatment response

**Style Designator:**

Female coupling half

**Thread Series Designator:**

Unjf second fluid end connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A531t0

**Mil-std (military Standard):**

Mil-a-8625 spec.