

View Online at <https://aerobasegroup.com/nsn/4730-01-546-0933>

Mounting Type:

Unthreaded hole top side

Mounting Hole Diameter:

0.500 inches

Mounting Hole Quantity:

4

Body Length:

16.000 inches

Body Height:

23.562 inches

Distance Between Mounting Hole Centers:

4.000 inches

End Application:

150psi simplex strainer 4 ips

Perforation Diameter:

0.188 inches

Perforation Quantity:

18.0 per square inch

Temperature Rating:

Between 85.0 degrees fahrenheit and 150.0 degrees fahrenheit

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

First Intake Connection Type:

Plain face flange top side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Discharge Connection Type:

Plain face flange top side

Distance From Bottom Of Body To Center Of Inlet:

16.000 inches

Center To Center Distance Between Connections:

16.000 inches

First Intake Flange Outside Diameter:

9.000 inches

First Intake Flange Shape Style:

Round w/unthreaded bolt holes

First Discharge Flange Shape Style:

Round w/unthreaded bolt holes

First Discharge Flange Outside Diameter:

9.000 inches

First Intake Flange Face Style:

Plain

First Discharge Flange Face Style:

Plain

First Intake Flange Thickness:

0.937 inches

First Discharge Flange Thickness:

0.937 inches

Special Features:

Material b61 bronze, basket monel, magnetic assembly

Material:

Copper alloy body

Media For Which Designed:

Water and fuel/oil, hydrocarbon

Style Designator:

Diverted flow basket strainer w/clamped cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000