

View Online at <https://aerobasegroup.com/nsn/4730-01-546-0933>

**Mounting Type:**

Unthreaded hole top side

**Mounting Hole Diameter:**

0.500 inches

**Mounting Hole Quantity:**

4

**Body Length:**

16.000 inches

**Body Height:**

23.562 inches

**Distance Between Mounting Hole Centers:**

4.000 inches

**End Application:**

150psi simplex strainer 4 ips

**Perforation Diameter:**

0.188 inches

**Perforation Quantity:**

18.0 per square inch

**Temperature Rating:**

Between 85.0 degrees fahrenheit and 150.0 degrees fahrenheit

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Filtering Media Design:**

Perforated single filtering media response

**First Intake Connection Type:**

Plain face flange top side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Discharge Connection Type:**

Plain face flange top side

**Distance From Bottom Of Body To Center Of Inlet:**

16.000 inches

**Center To Center Distance Between Connections:**

16.000 inches

**First Intake Flange Outside Diameter:**

9.000 inches

**First Intake Flange Shape Style:**

Round w/unthreaded bolt holes

**First Discharge Flange Shape Style:**

Round w/unthreaded bolt holes

**First Discharge Flange Outside Diameter:**

9.000 inches

**First Intake Flange Face Style:**

Plain

**First Discharge Flange Face Style:**

Plain

**First Intake Flange Thickness:**

0.937 inches

**First Discharge Flange Thickness:**

0.937 inches

**Special Features:**

Material b61 bronze, basket monel, magnetic assembly

**Material:**

Copper alloy body

**Media For Which Designed:**

Water and fuel/oil, hydrocarbon

**Style Designator:**

Diverted flow basket strainer w/clamped cover

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000