NSN 4730-01-548-0348

Tube Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-548-0348

| Thread Class: |
|---|
| 3a 2nd end |
| End Application: |
| Misc bulk items |
| Connection Style: |
| Socket (tube) 1st end |
| Connection Type: |
| Unthreaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 24 2nd end |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch single response |
| Thread Size: |
| 0.438 inches 2nd end |
| Seat Angle: |
| 8.1 degrees 2nd end |
| Outside Diameter Tube Accommodated: |
| 0.250 inches all ends |
| Tubing Wall Thickness For Which Designed: |
| 0.022 inches 1st end |
| Nominallength: |
| 0.802 inches |
| Product Name: |
| Adapter, male beam seal to weld |
| Special Features: |
| Male beam seal tosocket weld |
| Material: |
| Titanium alloy |
| Material Specification: |
| 81343-ams4965 6al-4v federal specification all material responses |
| Style Designator: |
| Threaded external rigid, threaded internal swivel |
| Thread Series Designator: |
| Unjs 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A080b0 |