

View Online at <https://aerobasegroup.com/nsn/4730-01-559-1757>

Thread Class:

3a 1st end bulkhead

Reducer Type:

Concentric

End Application:

Hh/uh1 helicopter

Connection Style:

Flareless (tube) 2nd end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

20 1st end bulkhead

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.563 inches 2nd end

Seat Angle:

24.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.375 inches 2nd end

Nominallength:

1.750 inches

Product Name:

Fitting, union, standard and reducer, bulkhead, flareless

Special Features:

Wrenching facility distance across flats .802 to .815

Material:

Aluminum alloy

Material Specification:

Ams 4124 type 7075-t7351 assn standard single material response or ams-qq-a-225/9 type 7075-t73 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ams 2472 assn standard single treatment response or mil-s-8625, type ii, class 2; dye brown military specification single treatment response

Thread Series Designator:

Unjf 1st end bulkhead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-s-8625 spec.