

View Online at <https://aerobasegroup.com/nsn/4730-01-576-5029>

**Thread Class:**

2a 2nd end

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**End Application:**

2320-01-552-7762, truck, wrecker

**Connection Style:**

Swivel nut, gasket seal (hose) 2nd end

**Connection Type:**

Unthreaded external tube 1st end

**Thready Qty Per Inch (tpi):**

18 2nd end

**Maximum Operating Pressure:**

6000.0 pounds per square inch single response

**Thread Size:**

0.560 inches 2nd end

**Width Across Flats:**

0.880 inches center bulkhead

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Nominallength:**

1.470 inches

**Product Name:**

Adapter, straight thread

**Special Features:**

Nha-12506098; material-low carbon steel, nitrile o-ring (shore a 90, class -1); temp range m40f degrees to 180f deg

**Material:**

Steel body

**Surface Treatment:**

Zinc body

**Surface Treatment Specification:**

Astm b633, ty ii, fe/zn8, cr+6 free zinc assn standard single treatment response bolt

**Style Designator:**

Swaged and threaded internal swivel

**Thread Series Designator:**

Un 2nd end and unf 2nd end

**Specification Data:**

81343-sae j1453 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0