

View Online at <https://aerobasegroup.com/nsn/4730-01-576-5029>

Thread Class:

2a 2nd end

Maximum Operating Temp:

180.0 degrees fahrenheit single response

End Application:

2320-01-552-7762, truck, wrecker

Connection Style:

Swivel nut, gasket seal (hose) 2nd end

Connection Type:

Unthreaded external tube 1st end

Thready Qty Per Inch (tpi):

18 2nd end

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

0.560 inches 2nd end

Width Across Flats:

0.880 inches center bulkhead

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Nominallength:

1.470 inches

Product Name:

Adapter, straight thread

Special Features:

Nha-12506098; material-low carbon steel, nitrile o-ring (shore a 90, class -1); temp range m40f degrees to 180f deg

Material:

Steel body

Surface Treatment:

Zinc body

Surface Treatment Specification:

Astm b633, ty ii, fe/zn8, cr+6 free zinc assn standard single treatment response bolt

Style Designator:

Swaged and threaded internal swivel

Thread Series Designator:

Un 2nd end and unf 2nd end

Specification Data:

81343-sae j1453 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0