

View Online at <https://aerobasegroup.com/nsn/4730-01-578-7541>

**Thread Class:**

2a center bulkhead

**End Application:**

Global hawk

**Connection Style:**

Plain (hose) 1st end

**Leg Length:**

2.000 inches 1st end

**Connection Type:**

Unthreaded external hose all ends

**Maximum Operating Pressure:**

125.0 pounds per square inch single response

**Flow Angle:**

60.0 degrees

**Product Name:**

60 degrees bulkhead assembly

**Special Features:**

Id 0.970; 1st end od 1.0663, 2nd 'nd od 1.263; hex nut width across flats 2.03; threads 1 3/8-12-unf-2; item dyed magenta; min thickness for bulkhead 0.05 by 1.406 thru; assembly consit of body 1 p/n lc423-16ae, nut 1 p/n lc015-16ae and locking pellet 1 p/n sd027-003

**Material:**

Aluminum alloy nut

**Material Specification:**

Ams-qq-a-225/6, t851, t8511 or t8510 assn standard single material response nut or ams-qq-a-200/3 assn standard single material response nut

**Surface Treatment:**

Anodize nut

**Surface Treatment Specification:**

Mil-c-5541. Cl3 military specification single treatment response body

**Style Designator:**

Elbow

**Thread Series Designator:**

Unf center bulkhead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-c-5541 spec.