

View Online at <https://aerobasegroup.com/nsn/4730-01-578-7541>

Thread Class:

2a center bulkhead

End Application:

Global hawk

Connection Style:

Plain (hose) 1st end

Leg Length:

2.000 inches 1st end

Connection Type:

Unthreaded external hose all ends

Maximum Operating Pressure:

125.0 pounds per square inch single response

Flow Angle:

60.0 degrees

Product Name:

60 degrees bulkhead assembly

Special Features:

Id 0.970; 1st end od 1.0663, 2nd 'nd od 1.263; hex nut width across flats 2.03; threads 1 3/8-12-unf-2; item dyed magenta; min thickness for bulkhead 0.05 by 1.406 thru; assembly consit of body 1 p/n lc423-16ae, nut 1 p/n lc015-16ae and locking pellet 1 p/n sd027-003

Material:

Aluminum alloy nut

Material Specification:

Ams-qq-a-225/6, t851, t8511 or t8510 assn standard single material response nut or ams-qq-a-200/3 assn standard single material response nut

Surface Treatment:

Anodize nut

Surface Treatment Specification:

Mil-c-5541. C13 military specification single treatment response body

Style Designator:

Elbow

Thread Series Designator:

Unf center bulkhead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A080b0

Mil-std (military Standard):

Mil-c-5541 spec.