

View Online at <https://aerobasegroup.com/nsn/4730-01-578-7547>

Thread Class:

2a center bulkhead

Seat Type:

Recessed

End Application:

Global hawk

Connection Style:

Grooved (hose) all ends

Connection Type:

Unthreaded external hose all ends

Maximum Operating Pressure:

125.0 pounds per square inch single response

Nominallength:

1.954 inches

Product Name:

Bulkhead fitting assembly

Special Features:

Id is 0.970; od is 1.060; threads 1 3/8-12unf-2; hex nut distance across flats 1.875; min distance between nuts for bulkhead is 1.406; assembly consist of body p/n lc188-16ae, nut p/n 6c015-16ae and locking pellet p/n sd027-003; tube size is 1.00; item is dyed magenta

Material:

Aluminum alloy nut

Material Specification:

Ams-qq-a-225/6 assn standard single material response nut or ams-qq-a-200/3 assn standard single material response nut

Surface Treatment:

Anodize nut and chromate nut

Surface Treatment Specification:

Mil-a-8625, type ii military specification 1st treatment response nut and mil-c-5541, class 3 military specification 2nd treatment response nut

Style Designator:

Rigid, short center wrenching facility

Thread Series Designator:

Unf center bulkhead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.