

View Online at <https://aerobasegroup.com/nsn/4730-01-584-2895>

**Thread Class:**

2a center bulkhead

**End Application:**

Global hawk

**Connection Style:**

Grooved (hose) all ends

**Connection Type:**

Unthreaded external tube all ends

**Thready Qty Per Inch (tpi):**

12 center bulkhead

**Maximum Operating Pressure:**

125.0 pounds per square inch single response

**Thread Size:**

0.938 inches center bulkhead

**Inside Diameter Hose Accommodated:**

0.625 inches all ends

**Nominallength:**

1.794 inches

**Special Features:**

Is is 0.595; od is 0.706; hex nut distance across flats 1.500; min distance between nuts for bulkhead is 0.968; assembly consists of body p/n lc534-10ae, nut p/n lc015-10ae, and locking pellet sd027-003

**Material:**

Aluminum alloy nut

**Material Specification:**

Ams-qq-a-225/6, 2024-t851, t8511, t8510 assn standard single material response body or ams-qq-a-200/3, 2024-t851, t8511, t8510 assn standard single material response body

**Surface Treatment:**

Anodize nut and chromate magnesium nut

**Surface Treatment Specification:**

Mil-a-8625, type ii, dyed magenta military specification 1st treatment response nut and mil-c-5541 class3 military specification 2nd treatment response nut

**Style Designator:**

Rigid, short center wrenching facility

**Thread Series Designator:**

Un center bulkhead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-a-8625 spec