NSN 4730-01-585-2356

Pipe Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-01-585-2356

End Application:
4110-01-534-7675, mobile int coll sys
External Thread Size:
0.500
Internal Thread Size:
0.250
Working Pressure And Service Type:
125.0 pounds per square inch steam err-100 err-100
Working Tempurature And Service Type:
400.0 degrees fahrenheit steam
External Screw Thread Series Designator:
Npt
External Thread Direction:
Right-hand
Internal Screw Thread Series Designator:
Npt
Internal Thread Direction:
Right-hand
Product Name:
Low-pressure threaded pipe fitting male 1/2 in x female 1/4 in hex reducing bushing
Special Features:
Use standard wall (schedule 40) brass threaded
Material:
Brass
Material:
Copper alloy
Style Designator:
Outside hexagon
Supplementary Features:
pressure at 72 degrees f is 200.0 psi; 1/4 in internal has 18 threads per inch, 0.40 in thread engagement; 1/2 in external has 14 threads
per inch, 0.53 in thread engagement
Specification Data:
80204-ansi b1 20 1 and ansi b16 15 professional/industrial association specification and 81346-astm b584 professional/industrial association
specification and 05047-asme b1 20 1 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T385-k