## NSN 4730-01-606-5708

Tube Tee - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-606-5708 **Thread Class:** 3a all ends **Connection Style:** Flared (tube) all ends Leg Length: 0.976 inches 2nd end **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 20 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees **Outside Diameter Tube Accommodated:** 0.312 inches all ends **Reduced Passage Inside Diameter:** 0.250 inches 1st end bulkhead **Product Name:** Fitting, tee standard and reducer, bulkhead on run, flared **Special Features:** Similar to 4730-01-598-3336 except for high purity aluminum coating finish, p/n as1033w050504 Material: Aluminum alloy 7075 **Material Specification:** Ams4041 or assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-dtl-8344, cl 3, ty ii assn standard single treatment response **Style Designator:** Tee **Thread Series Designator:** Unjf all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4730-01-606-5708

Tube Tee - Page 2 of 2



	izat	

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-dtl-8344 spec.