

View Online at <https://aerobasegroup.com/nsn/4730-01-625-2995>

Thread Class:

3a 2nd end

Connection Style:

Gasket seal (hose) 2nd end

Flange Shape:

Hexagon 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

20 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.4375 inches 2nd end

Thickness:

0.15 inches 2nd end

Width Across Flats:

0.6875 inches 2nd end

Outside Diameter Tube Accommodated:

0.4375 inches 1st end

Nominallength:

1.032 inches

Product Name:

Fitting assembly, flared tube end to modified screen end

Special Features:

Bushing is made of 2024-t4 aluminum per qq-a-225 and is anodized iaw mil-a-8625, type ii, class 1; screen is made of 316 cres and is annealed

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225 federal specification single material response body

Surface Treatment:

Anodize body

Surface Treatment Specification:

Mil-a-8625, type ii, class 1 military specification single treatment response body

Style Designator:

Flared and flareless w/ center wrenching facility

Thread Series Designator:

Unjf 2nd end

Specification Data:

1sfn4-ngf503gm manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.