

View Online at <https://aerobasegroup.com/nsn/4730-01-626-4752>

**Connection Style:**

Flared (tube) all ends

**Leg Length:**

1.117 inches 2nd end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

14 all ends

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.8750 inches all ends

**Flow Angle:**

45.0 degrees

**Outside Diameter Tube Accommodated:**

0.625 inches all ends

**Special Features:**

Coat with high purity aluminum per mil-dtl-83488, class3, type ii with maximum coating thickness of .0005. Glass bead peen pressure shell be 25 psi maximum.

**Material:**

Aluminum alloy 7075

**Material Specification:**

Ams4141 assn standard single material response or ms-qq-a-367 assn standard single material response or ms4124 assn standard single material response or ws-qq-a-225/9 assn standard single material response

**Surface Treatment Specification:**

Mil-dtl-83488, class3, type ii military standard single treatment response

**Style Designator:**

Flared w/ bulkhead thread

**Thread Series Designator:**

Unjf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-dtl-83488 spec.