

View Online at <https://aerobasegroup.com/nsn/4730-01-626-4752>

Connection Style:

Flared (tube) all ends

Leg Length:

1.117 inches 2nd end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

14 all ends

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.8750 inches all ends

Flow Angle:

45.0 degrees

Outside Diameter Tube Accommodated:

0.625 inches all ends

Special Features:

Coat with high purity aluminum per mil-dtl-83488, class3, type ii with maximum coating thickness of .0005. Glass bead peen pressure shell be 25 psi maximum.

Material:

Aluminum alloy 7075

Material Specification:

Ams4141 assn standard single material response or ms-qq-a-367 assn standard single material response or ms4124 assn standard single material response or ws-qq-a-225/9 assn standard single material response

Surface Treatment Specification:

Mil-dtl-83488, class3, type ii military standard single treatment response

Style Designator:

Flared w/ bulkhead thread

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-dtl-83488 spec.