

View Online at <https://aerobasegroup.com/nsn/4730-01-626-9125>

**Thread Class:**

3a all ends

**Connection Style:**

Flared (tube) all ends

**Leg Length:**

1.789 inches 2nd end

**Connection Type:**

Threaded external tube all ends

**Thready Qty Per Inch (tpi):**

12 all ends

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

1.0625 inches all ends

**Tubing Wall Thickness For Which Designed:**

0.750 inches all ends

**Product Name:**

Fitting, tee, standard and reducer, bulkhead on side, flared

**Special Features:**

This fitting cannot be used in ports; non-reducer style end fitting

**Material:**

Aluminum alloy 7075

**Material Specification:**

7075-t73 per ams4141 national std/spec 1st material response or 7075-t73 per qq-a-367 federal specification 2nd material response or 7075-t7351 per ams4124 national std/spec 3rd material response or 7075-t73 per qq-a-225/9 federal specification 4th material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ams2472 national std/spec 1st treatment response or mil-a-8625, type ii, class 2, dye brown, duplex seal per procurement specification military specification 2nd treatment response

**Style Designator:**

Tee

**Thread Series Designator:**

Unj all ends

**Specification Data:**

81343-as1039 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-a-8625 spec.