

View Online at <https://aerobasegroup.com/nsn/4730-01-626-9125>

Thread Class:

3a all ends

Connection Style:

Flared (tube) all ends

Leg Length:

1.789 inches 2nd end

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

1.0625 inches all ends

Tubing Wall Thickness For Which Designed:

0.750 inches all ends

Product Name:

Fitting, tee, standard and reducer, bulkhead on side, flared

Special Features:

This fitting cannot be used in ports; non-reducer style end fitting

Material:

Aluminum alloy 7075

Material Specification:

7075-t73 per ams4141 national std/spec 1st material response or 7075-t73 per qq-a-367 federal specification 2nd material response or 7075-t7351 per ams4124 national std/spec 3rd material response or 7075-t73 per qq-a-225/9 federal specification 4th material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ams2472 national std/spec 1st treatment response or mil-a-8625, type ii, class 2, dye brown, duplex seal per procurement specification military specification 2nd treatment response

Style Designator:

Tee

Thread Series Designator:

Unj all ends

Specification Data:

81343-as1039 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.