

View Online at <https://aerobasegroup.com/nsn/4730-01-642-4366>

**End Application:**

Mrap buffalo mk2a2

**Internal Thread Size:**

Npt0.125

**External Screw Thread Series Designator:**

Npt

**External Thread Direction:**

Right-hand

**Internal Screw Thread Series Designator:**

Npt

**Internal Thread Direction:**

Right-hand

**Product Name:**

Low-pressure brass pipe fittings with sealant

**Material:**

Copper alloy

**Style Designator:**

Outside hexagon

**Supplementary Features:**

pressure: 200 psi @ 72 degrees f; 125 psi @ 400 degrees f for steam; pipe nipples and pipe: threaded schedule 40 standard-wall brass; flanges: threaded class 150 low-pressure brass; hexagon head width: 1.19 inches; head height: 0.22 inches; length: 0.85 inches; 3/4 npt pipe size, 14 threads per inch, 0.55 inches thread engagement; 3/8 npt pipe size, 18 threads per inch, 0.41 inches thread engagement; additional specifications: male x female hex reducing bushings use with air, water, oil, natural gas, steam; rohs compliant; thread sealant is already applied to male threads; connections: npt

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T385-k