

View Online at <https://aerobasegroup.com/nsn/4810-00-004-0727>

Thread Direction:

Right-hand 1st end

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Open

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

0.470

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe 1st end

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

15.0 pounds per square inch

Thread Size:

2.000 inches 1st end

Voltage In Volts And Current Type:

26.0 dc

Special Features:

W/connector, plug, electrical, ms3101f12s3p attached

Material:

Aluminum flow control device

Special Test Features:

Fungus and moisture proof, organism group ii

Style Designator:

Straight thru

Test Data Document:

81349-mil-e-5272 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0