NSN 4810-00-007-2311

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Flow Control Device:

Bolt Hole Quantity:

Disk

Closed

6 all ends



View Online at https://aerobasegroup.com/nsn/4810-00-007-2311

Current Rating In Amps:
0.180
Valve Operation Method:
Solenoid
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
1.500 inches
Inlet/outlet Operating Pressure Differential:
100.0 pounds per square inch
Voltage In Volts And Current Type:
115.0 ac
Outside Diameter:
5.062 inches all ends
Face To Face Distance:
6.000 inches
Thickness:
0.500 inches all ends
Bolt Hole Diameter:
0.562 inches all ends
Bolt Circle Diameter:
3.938 inches all ends
Flange Face Design:
Plain all ends
Phase:
Single
Special Features:
For naval shipboard systems use
Frequency In Hertz:
60.0
Material:
Rubber butadiene-acrylonitrile class nbr flow control device and stainless steel flow control device

NSN 4810-00-007-2311

Solenoid Valve - Page 2 of 2



Sty					

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0