## NSN 4810-00-007-4738

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-007-4738

Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Closed
Connection Style:
Socket (tube) all ends
Current Rating In Amps:
0.170
Valve Operation Method:
Solenoid
Connection Type:
Unthreaded internal tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
100.0 pounds per square inch single response
Voltage In Volts And Current Type:
115.0 ac
Outside Diameter Tube Accommodated:
0.750 inches all ends
Phase:
Single
Special Features:
Manual override
Frequency In Hertz:
60.0
Material:
Steel comp 303 seat
Material Specification:
Astm b283 assn standard single material response body
Media For Which Designed:
Air 1st response
Surface Treatment:
Cadmium
Style Designator:
Straight thru
Test Data Document:
81349-mil-s-901 specification (includes engineering type b
excludes commercial catalogs, industry directories, and

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Shelf Life:

N/a

## NSN 4810-00-007-4738

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

