

View Online at <https://aerobasegroup.com/nsn/4810-00-056-2519>

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

71.0 degrees celsius single response

Connection Style:

Gasket sea (boss) all ends

Current Rating In Amps:

0.300

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss all ends

Mounting Position:

Horizontal

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Frequency In Hertz:

400.0

Material:

Magnesium alloy

Material Specification:

Mil-s-4040, group 1 military specification single material response

Media For Which Designed:

Hydraulic fluid, phosphate-ester base 2nd response

Style Designator:

Straight thru

Test Data Document:

81349-mil-s-4040 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-4040 spec.