NSN 4810-00-056-2907

Solenoid Valve - Page 1 of 2

Thread Class: 3b 1st end

Poppet

Thread Direction:
Right-hand 1st end
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-00-056-2907

Торрог
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
135.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Current Rating In Amps:
0.750
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
135.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Center To Center Distance:
1.000 inches
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Stainless steel
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end

NSN 4810-00-056-2907

Solenoid Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0