

View Online at <https://aerobasegroup.com/nsn/4810-00-075-1973>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Flared (tube) 1st end

Current Rating In Amps:

1.250

Valve Operation Method:

Solenoid

Flange Shape:

Round 2nd end

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

140.0 pounds per square inch single response

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Voltage In Volts And Current Type:

26.0 dc

Outside Diameter:

1.574 inches 2nd end

Thickness:

0.110 inches 2nd end

Flange Face Design:

Plain 2nd end

Outside Diameter Tube Accommodated:

1.000 inches 1st end

Special Features:

Oriface on first end 0.595 in. Min. 0.605 in. Maximum dia.

Material:

Steel seat

Media For Which Designed:

Air single response

Style Designator:

Straight thru

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0