NSN 4810-00-085-5077

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-085-5077

Thread Direction:

Right-hand all ends

Offset Distance:

1.000 inches

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

0.013

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

30.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Voltage In Volts And Current Type:

440.0 ac and 480.0 ac

Phase:

Single

Special Features:

Mtg bracket and 2 screws

Frequency In Hertz:

50.0 and 60.0

Material:

Steel flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Cross w/offset

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

2 adapter

Shelf Life:

N/a

NSN 4810-00-085-5077

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

