NSN 4810-00-094-8180

Demilitarization: Yes - demil/mli

Directional Control Linear Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-094-8180 **Thread Class:** 3b **End Connection Quantity: Valve Discharge Flow Rate:** 3.2 gallons per minute **End Application:** T.O. 9h8-14-99-83 fig 8 **Current Rating In Amps:** 1.2 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss **Maximum Operating Pressure And Media For Which Designed:** 3000.0 pounds per square inch hydraulic fluid, petroleum base **Thread Size:** 0.375 inches **Body Material:** Aluminum alloy **Criticality Code Justification:** Feat and agav **Maximum Operating Tempurature And Media For Which Designed:** 160.0 degrees fahrenheit hydraulic fluid, petroleum base **Voltage In Volts And Current Type:** 28.0 dc Flow Pattern Quantity: **Spool Position Quantity: Spool Quantity: Special Features:** Manufacturers suggested name is valve assembly, solenoid, 3 way, 2 position; operating temp abmient -65 to +160 degrees feg; weight 1.5 lbs; voltage range 18 to 28 vdc, 3 ports per and10050-6; 5.53 in. Lg., 1.81 in. Wide, 2.50 in. Ht.; elec connector an3102a-10sl-4p **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

NSN 4810-00-094-8180

Directional Control Linear Valve - Page 2 of 2



Fiig:

A506h0