

View Online at <https://aerobasegroup.com/nsn/4810-00-094-8188>

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Offset Distance:**

0.625 inches

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Closed

**Connection Style:**

Gasket sea (boss) 1st end

**Current Rating In Amps:**

0.200

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal tube 1st end

**Mounting Position:**

Vertical

**Thready Qty Per Inch (tpi):**

18 1st end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

60.0 degrees 1st end

**Voltage In Volts And Current Type:**

18.0 dc and 28.0 dc

**Outside Diameter Tube Accommodated:**

0.375 inches 1st end

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response

**Style Designator:**

Straight through w/offset

**Test Data Document:**

00502-ht25400 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A046b0