

View Online at <https://aerobasegroup.com/nsn/4810-00-094-8188>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Offset Distance:

0.625 inches

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Gasket sea (boss) 1st end

Current Rating In Amps:

0.200

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Mounting Position:

Vertical

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

60.0 degrees 1st end

Voltage In Volts And Current Type:

18.0 dc and 28.0 dc

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Stainless steel flow control device

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Straight through w/offset

Test Data Document:

00502-ht25400 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0