## NSN 4810-00-111-2561

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/psp/4810-00-111-2561

view Omine at http:	s://aerobasegroup.com/nsn/4610-00-111-2561
Thread Direction:	
Right-hand 1st end	
Offset Distance:	
0.500 inches	
Flow Control Devi	ce:
Poppet	
Flow Control Devi	ce Normal Operation Position:
Closed	
<b>Bolt Hole Quantity</b>	r:
2 2nd end	
Connection Style:	
Plain, optional en (p	pipe) 1st end
Width:	
0.938 inches 2nd e	nd
Length:	
1.562 inches 2nd e	nd
Current Rating In	Amps:
0.125	
Valve Operation M	lethod:
Solenoid	
Flange Shape:	
Oval with holes 2nd	I end
Connection Type:	
Threaded internal p	ipe 1st end
Mounting Position	ı:
Horizontal	
Thread Size:	
0.125 inches 1st er	nd
Voltage In Volts A	nd Current Type:
24.0 dc	
Thickness:	
1.375 inches 2nd e	nd
Bolt Hole Diamete	r:
0.312 inches 2nd e	nd
Bolt Circle Diamet	er:
1.156 inches 2nd e	nd
Flange Face Desig	ın:
Recessed with gas	ket groove 2nd end

**Recess Diameter:** 

0.562 inches 2nd end

**Recess Depth:** 

0.047 inches 2nd end

## NSN 4810-00-111-2561

Solenoid Valve - Page 2 of 2



Material:
Stainless steel flow control device
Style Designator:
Straight through w/offset
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0