NSN 4810-00-124-8564

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-124-8564

| Flow Control Device: |
|---|
| Diaphragm |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Bolted |
| Renewable Seat Ring Type: |
| Threaded |
| Connection Style: |
| Streamlined with one brazing ring (tube) all ends |
| Valve Operation Method: |
| Hydraulic |
| Connection Type: |
| Unthreaded internal tube all ends |
| Power Drive Operating Pressure: |
| 5.0 pounds per square inch |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Outside Diameter Tube Accommodated: |
| 0.375 inches all ends |
| Special Features: |
| Port centerline to valve top 3.750 in. |
| Material: |
| Nickel alloy stem |
| Material Specification: |
| Qq-c-390, alloy d4/d/ federal specification single material response body |
| Media For Which Designed: |
| Water, salt single response |
| Style Designator: |
| Straight thru |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |