

View Online at <https://aerobasegroup.com/nsn/4810-00-132-1834>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Gasket sea (boss) 1st end

Current Rating In Amps:

1.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

18 1st end

Inlet/outlet Operating Pressure Differential:

180.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Product Name:

Manufacturers suggested name is valve control engine air aux. Fuel system

Special Features:

Operating voltage 18to 30 vdc; operating inlet pressure 35-200 psig; ambient pressure at seal level to 20, 000 ft. Pressure altitude; temperature fluid range -65 to 500 degrees feh; ambient temperature is -65 to 160 degrees feh; fluid turbine compressor bleed air; relief valve cracking

Material:

Stainless steel seat

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0