## NSN 4810-00-162-2948

Solenoid Valve - Page 1 of 2



C
View Online at https://aerobasegroup.com/nsn/4810-00-162-2948
Thread Class:
3a 2nd end
Thread Direction:
Right-hand 2nd end
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
External seat for gasket seal (boss) 2nd end
Current Rating In Amps:
1.700
Valve Operation Method:
Solenoid
Flange Shape:
Round 1st end
Connection Type:
Threaded external boss 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
12 2nd end
Maximum Operating Pressure:
60.0 pounds per square inch single response
Thread Size:
1.062 inches 2nd end
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Outside Diameter:
0.989 inches 1st end
Thickness:
0.065 inches 1st end
Flange Face Design:

## Plain 1st end

**Outside Diameter Tube Accommodated:** 

0.750 inches 2nd end

Material:

Steel comp 303 seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4810-00-162-2948

Solenoid Valve - Page 2 of 2



Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Un 2nd end
Reference Number Differentiating Characteristics:
As differentiated by the source control dwg no.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A046b0