NSN 4810-00-164-3240

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-164-3240 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.028 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:** 0.300 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Steel flow control device **Material Specification:** Qq-a-225/4 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Surface Treatment:** Anodize **Style Designator:**

Straight thru **Thread Series Designator:** Anpt all ends

NSN 4810-00-164-3240

Solenoid Valve - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0