NSN 4810-00-200-2586

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-200-2586

Pipe Size Accommodated:
1.250 inches 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
1.125 inches
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.139
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
11-1/2 1st end
Inlet/outlet Operating Pressure Differential:
Between 10.0 pounds per square inch and 300.0 pounds per square inch
Maximum Operating Pressure:
350.0 pounds per square inch single response
Thread Size:
1.250 inches 1st end
Voltage In Volts And Current Type:
120.0 ac
Phase:
Single
Special Features:
Explosion-proof-watertight solenoid enclosure
Frequency In Hertz:
60.0
Material:
Plastic polytetrafluoroethylene seat
Style Designator:

Straight thru

NSN 4810-00-200-2586

Solenoid Valve - Page 2 of 2



Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0