NSN 4810-00-200-2616

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-200-2616

Pipe Size Accommodated:
1.500 inches 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
1.125 inches
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
11-1/2 1st end
Inlet/outlet Operating Pressure Differential:
Between 5.0 pounds per square inch and 125.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
1.500 inches 1st end
Phase:
Single
Special Features:
Explosion-proof-watertight solenoid enclosure
Material:
Rubber flow control device
Material Specification:
Mil-r-1149, ty2, cl1 military specification single material response seat
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N1/-

N/a

NSN 4810-00-200-2616

Solenoid Valve - Page 2 of 2



ı	Ini	4	Ωf	RЛ		۰.	ıre	
ι	JNI	IT '	UI.	IVI	ea	รเ	ıre	

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-1149 spec.