## NSN 4810-00-200-2628

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-200-2628

| Pipe Size Accommodated:   |
|---|
| 0.375 inches 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Aperture Diameter:  |
| 0.375 inches  |
| Flow Control Device:  |
| Diaphragm   |
| Flow Control Device Normal Operation Position:                            |
| Closed  |
| Maximum Operating Temp:   |
| 200.0 degrees fahrenheit single response                                  |
| Connection Style:   |
| Plain, optional en (pipe) 1st end   |
| Valve Operation Method:   |
| Solenoid  |
| Connection Type:  |
| Threaded internal pipe 1st end  |
| Mounting Position:  |
| Horizontal  |
| Thready Qty Per Inch (tpi):   |
| 18 1st end  |
| Inlet/outlet Operating Pressure Differential:                             |
| 15.0 pounds per square inch   |
| Maximum Operating Pressure:   |
| 250.0 pounds per square inch single response                              |
| Thread Size:  |
| 0.375 inches 1st end  |
| Phase:  |
| Single  |
| Material:   |
| Rubber flow control device  |
| Material Specification:   |
| Mil-r-1149, ty2, cl1 military specification single material response seat |
| Style Designator:   |
| Straight thru   |
| Thread Series Designator:   |
| Npt 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 4810-00-200-2628

Solenoid Valve - Page 2 of 2



| _  |     |         |     |     |    |  |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | <br>tor | 172 | + 1 | nn |  |
|    |     |         |     |     |    |  |

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-1149 spec.