## NSN 4810-00-200-2766

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-200-2766

Pipe Size Accommodated:
2.000 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.708
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
11-1/2 1st end
Inlet/outlet Operating Pressure Differential:
180.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
2.000 inches 1st end
Voltage In Volts And Current Type:
120.0 ac
Phase:
Single
Frequency In Hertz:
60.0
Material:
Copper alloy body
Media For Which Designed:
Steam single response
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
THE TOLOTIO

## NSN 4810-00-200-2766

Solenoid Valve - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0