

View Online at <https://aerobasegroup.com/nsn/4810-00-200-2800>

Pipe Size Accommodated:

1.000 inches 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

1.000 inches

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

0.467

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

11-1/2 1st end

Inlet/outlet Operating Pressure Differential:

Between 5.0 pounds per square inch and 125.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

1.000 inches 1st end

Voltage In Volts And Current Type:

24.0 dc

Special Features:

Radiation resistant, operable in high temperature and highly humid conditions, explosion proof, watertight, solenoid enclosure

Material:

Rubber flow control device

Material Specification:

Mil-r-1149, ty2, cl1 military specification single material response flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-1149 spec.