

View Online at <https://aerobasegroup.com/nsn/4810-00-200-2839>

Pipe Size Accommodated:

0.375 inches 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

0.625 inches

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

0.050

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

18 1st end

Inlet/outlet Operating Pressure Differential:

Between 5.0 pounds per square inch and 200.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.375 inches 1st end

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

Explosion-proof-watertight solenoid enclosure

Frequency In Hertz:

60.0

Material:

Rubber flow control device

Material Specification:

Rubber, buna-n assn standard single material response seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0