NSN 4810-00-201-2887



Solenoid Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4810-00-201-2887
Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.250 inches
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
267.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.250
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
14 2nd end
Inlet/outlet Operating Pressure Differential:
300.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

Flow control device plunger, levered

Frequency In Hertz:

60.0

Material:

Copper alloy body

Media For Which Designed:

Water-oil-gas single response

NSN 4810-00-201-2887

Solenoid Valve - Page 2 of 2



Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 brazing ring and 1 tailpiece
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0