

View Online at <https://aerobasegroup.com/nsn/4810-00-201-8732>

**Flow Control Device:**

Disk

**Flow Control Device Normal Operation Position:**

Closed

**Renewable Seat Ring Type:**

Threaded

**Connection Style:**

Streamlined with one brazing ring (tube) all ends

**Current Rating In Amps:**

0.170

**Valve Operation Method:**

Solenoid

**Connection Type:**

Unthreaded internal tube all ends

**Mounting Position:**

Horizontal or vertical

**Voltage In Volts And Current Type:**

115.0 ac

**Outside Diameter Tube Accommodated:**

1.500 inches all ends

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Stainless steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device

**Material Specification:**

Astm b140 assn standard single material response seat

**Style Designator:**

Straight thru

**Test Data Document:**

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0