

View Online at <https://aerobasegroup.com/nsn/4810-00-202-6408>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

0.250 inches

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Closed

Renewable Seat Ring Type:

Threaded

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

20 1st end

Inlet/outlet Operating Pressure Differential:

40.0 pounds per square inch

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Voltage In Volts And Current Type:

14.0 dc and 18.0 dc

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Stainless steel seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0