

View Online at <https://aerobasegroup.com/nsn/4810-00-203-6565>

Thread Direction:

Right-hand all ends

Aperture Diameter:

0.172 inches

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

15.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Special Features:

W/two 0.193 in.Mtg hole through body

Material:

Steel comp 302 flow control device and rubber synthetic flow control device

Material Specification:

Mil-s-7720 military specification 1st material response flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Anpt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-s-7720 spec.