

View Online at <https://aerobasegroup.com/nsn/4810-00-203-6565>

**Thread Direction:**

Right-hand all ends

**Aperture Diameter:**

0.172 inches

**Flow Control Device:**

Disk

**Flow Control Device Normal Operation Position:**

Closed

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

15.0 pounds per square inch single response

**Thread Size:**

0.125 inches all ends

**Voltage In Volts And Current Type:**

18.0 dc and 30.0 dc

**Special Features:**

W/two 0.193 in.Mtg hole through body

**Material:**

Steel comp 302 flow control device and rubber synthetic flow control device

**Material Specification:**

Mil-s-7720 military specification 1st material response flow control device

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Anpt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0

**Mil-std (military Standard):**

Mil-s-7720 spec.