NSN 4810-00-204-1575

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-204-1575

Thread Class:3b 1st endThread Direction:Right-hand 1st endAperture Diameter:0.250 inchesFlow Control Device:DiaphragmMaximum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Thread Direction:Right-hand 1st endAperture Diameter:0.250 inchesFlow Control Device:DiaphragmMaximum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endMottage In Volts And Current Type:24.0 deMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Sizei steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Right-hand 1st endAperture Diameter:0.250 inchesFlow Control Device:DiaphragmMaximum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Straight thruChread Series Designator:Chread Series Designator:Chread Series Designator:Chread Series Designator:Chread Series Designator:Chread Series Designator:Chread Series Designator:Chr
Aperture Diameter:0.250 inchesFlow Control Device:DiaphragmMaximum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 deMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStaright thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
0.250 inches Flow Control Device: Diaphragm Maximum Operating Temp: 300.0 degrees fahrenheit single response Connection Style: Gasket sea (boss) 1st end Valve Operation Method: Solenoid Connection Type: Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Syle Designator: Straight thru Chread Series Designator: Unjf 1st end
Flow Control Device: Diaphragm Maximum Operating Temp: 300.0 degrees fahrenheit single response Connection Style: Gasket sea (boss) 1st end Valve Operation Method: Solenoid Connection Type: Threaded internal boss 1st end Mounting Position: Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
DiaphragmMaxinum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruInread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Maximum Operating Temp:300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruItread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
300.0 degrees fahrenheit single responseConnection Style:Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Connection Style: Gasket sea (boss) 1st end Valve Operation Method: Solenoid Connection Type: Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Gasket sea (boss) 1st endValve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStaright thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Valve Operation Method:SolenoidConnection Type:Threaded internal boss 1st endMounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Solenoid Connection Type: Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Connection Type: Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Threaded internal boss 1st end Mounting Position: Horizontal Thready Qty Per Inch (tpi): 20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Mounting Position:HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
HorizontalThready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Thready Qty Per Inch (tpi):20 1st endMaximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruChread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
20 1st end Maximum Operating Pressure: 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Maximum Operating Pressure:750.0 pounds per square inch single responseThread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStraight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
 750.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Thread Size:0.437 inches 1st endVoltage In Volts And Current Type:24.0 dcMaterial:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
0.437 inches 1st end Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Voltage In Volts And Current Type: 24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
24.0 dc Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Material:Stainless steel seatMedia For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Media For Which Designed:Fuel/oil, hydrocarbon single responseSurface Treatment:AnodizeStyle Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Fuel/oil, hydrocarbon single response Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Surface Treatment: Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Anodize Style Designator: Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Style Designator:Straight thruThread Series Designator:Unjf 1st endReference Number Differentiating Characteristics:
Straight thru Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Thread Series Designator: Unjf 1st end Reference Number Differentiating Characteristics:
Unjf 1st end Reference Number Differentiating Characteristics:
Reference Number Differentiating Characteristics:
-
As differentiated by source control drawing
Shelf Life:
N/a
Unit Of Measure:

NSN 4810-00-204-1575

Solenoid Valve - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

