NSN 4810-00-221-4448

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-221-4448

Pipe Size Accommodated:
1.500 inches 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
1.250 inches
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.140 and 0.128
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
11-1/2 1st end
Inlet/outlet Operating Pressure Differential:
Between 5.0 pounds per square inch and 125.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
1.500 inches 1st end
Voltage In Volts And Current Type:
110.0 ac and 120.0 ac
Phase:
Single
Frequency In Hertz:
50.0 and 60.0
Material:
Rubber flow control device
Material Specification:
Mil-r-1149, ty2, cl1 military specification single material response seat
Media For Which Designed:

Water-oil-gas single response

NSN 4810-00-221-4448

Solenoid Valve - Page 2 of 2



Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

Mil-std (military Standard):

Mil-r-1149 spec.