NSN 4810-00-230-3579

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-230-3579

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Flared (tube) all ends
Current Rating In Amps:
0.700
Valve Operation Method:
Solenoid
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
37.0 degrees all ends
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Special Features:
Supports grumman a-10 aircraft
Material:
Stainless steel flow control device
Material Specification:
66 federal standard single material response body
Media For Which Designed:
Air single response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Style Designator:
Straight thru

NSN 4810-00-230-3579

Solenoid Valve - Page 2 of 2



Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0