NSN 4810-00-248-6467

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-248-6467

Pipe Size Accommodated:
0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.750 inches
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
20.0 degrees fahrenheit 2nd response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.130
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 1st end
Maximum Operating Pressure:
200.0 pounds per square inch 2nd response
Thread Size:
0.750 inches 1st end
Voltage In Volts And Current Type:
208.0 ac and 240.0 ac
Phase:
Single
Special Features:
Waterproofed coil assembly
Frequency In Hertz:
50.0 and 60.0
Material:
Rubber synthetic flow control device
Material Specification:
Mil-p-5315, rubber, synthetic military specification single material response flow control device
Media For Which Designed:
Air 1st response
•

NSN 4810-00-248-6467

Solenoid Valve - Page 2 of 2

Style Designator:

Straight thru

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-p-5315 spec.

