

View Online at <https://aerobasegroup.com/nsn/4810-00-279-5745>

Offset Distance:

6.7000 inches

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

End Application:

Applicable t.O. 9h17-3-8-3

Current Rating In Amps:

1.500

Valve Operation Method:

Solenoid

Connection Type:

Threaded external boss 1st end

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Voltage In Volts And Current Type:

28.0 dc

Product Name:

Gun drive hydraulic flow regulator

Special Features:

Dimensions: length 6.7 in., height 5.30 in., width 2.25, weight 2.60 lbs; pressures: operating 3000 psig, proof 4500 psig, burst 7500 psig, rated flow solenoid deenergized 28.5 gpm, solenoid energized 19.0 gpm, amperage maximum 1.5 amp at 29 vdc, voltage 48 vdc

Material:

Aluminum alloy body

Media For Which Designed:

Hydraulic fluid, petroleum base 2nd response

Style Designator:

Straight thru

Supplementary Features:

Media is hydraulic fluid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0